Saegertown Borough

603 Erie Street, Po Box 558, Saegertown, PA 16433 • E-mail: saegertown@saegertownpa.com
Borough Building Phone: 814.763.4600 • Borough Building Fax: 814.763.2250

Zoning Officer: Gary Johnson 814-282-1368

DEMOLITIONS	
Location of property	Parcel #
Owner name:	Phone
Owner Address:	
Contractor name, address	Phone
Description of project	
One (1) copy of this application. Three (3) copies of a Plot Plant location and the shape of building (s) to be demolist Note: 1. All utilities must be disconneted. Appropriate warning/safety and a Burning is NOT permitted. 4. Basement, if present, must be	lan (Drawing), drawn to scale, showing the actual dimensions, the lot, with exact dimensions and location on the lot of the existing hed. cted barriers must be in place filled with clean "dirt", tamped, NOT construction debris I floors must be broken open to allow drainage
	roject cost of \$10,000; over \$10,000, times .005; max. \$500
CCI Required: Yes No	CCI Phone Number: 814-671-9413
• Notes	
Applie	cant acknowledgement and signature
submit in connection with the above-	nd the rules and regulations of Saegertown Borough, that all information I referenced project is true and correct, and I hereby agree that all applicable ad the laws of the Commonwealth of Pennsylvania will be complied with.
Signature	Date
Print name	Title

Customer Assistance Guide Building Permit Application Submittal Requirements

DEMOLITION CONSTRUCTION GUIDELINES

- Notify PA One Call at 800-242-1766 or at www.paonecall.org at least 3 days prior to start of any demolition or excavation.
- Identify the type and location of site utilities such as gas, electric, water service lateral, public sewer lateral, on-lot well or on-lot sewer system on the site plan.
- Utility Disconnections: Service utility connections shall be disconnected and capped in accordance with the approved rules and requirements of the applicable governing authority. International Building Code Section 3303.6.
- Identify on the site plan if any existing underground or aboveground storage tanks (combustible and flammable liquids) are present on the property. A separate permit shall be applied for and obtained prior to removal of any storage tanks. Permit shall be obtained from the Pennsylvania Department of Labor and Industry.
- Asbestos shall be removed in accordance with Pennsylvania Department of Environmental Protection
 Air Quality regulations. View the department's website at
 http://www.depweb.state.pa.us/dep/site/default.asp. Asbestos removal is regulated by the Department
 of Labor and Industry. Call Pennsylvania Department of Labor and Industry at 717-772-3396 for more
 information.
- Pedestrian Protection: The work of demolishing and building shall not commence until pedestrian protection is in place. Refer to Section 3306 of the 2009 IBC for specific protection requirements. IBC Section 3303.2
- Site Maintenance: Where a structure has been demolished or removed, the vacant lot shall be filled and maintained to the existing grade. Only clean fill is to be used in backfilling of demolished structures. IBC Section 3303.4.
- Water accumulation: Provisions shall be made to prevent the accumulation of water or damage to any foundations on the premises or the adjoining property. IBC 3303.5
- Future construction (if applicable) requires backfilling with approved engineered fill or excavation to virgin soil.

DEMOLITION PERMIT CHECKLIST AND CONSTRUCTION GUIDELINES

Complete the following checklist for the building demolition. Items that require an acknowledgement only mark with your initials. Items which do not apply, mark with "N/A" or not applicable.

(Completed permit application form with the required permit fee.
	Three (3) site plans clearly identifying the location and footprint square footage of the structure(s) being
(demolished. (Sketches are acceptable)
]	Public Water connection lines must be removed to the curb box.
A	Acknowledge that the electrical service has been disconnected by the serving utility.
V	When on-lot septic systems are present: (1) Tanks must be pumped. (2) Any associated piping must be
1	removed and properly disposed of and (3) Tanks must be removed and properly disposed of or
;	abandoned in-place with holes punched in the tank bottom and filled with clean fill.
V	When public sewer is present and the lateral is being abandoned: Laterals must be capped at the public
1	main as directed by local sewer authority.
(On-lot wells to be abandoned shall have the pump removed: the shaft shall be filled with clean stone and
1	permanently capped 12" below finished grade.
Authori	zed Agent/Property Owner SignatureDate: